



FULL LINE ALUMINUM CO₂ CYLINDERS

All Safe Global offers a complete range of high-quality aluminum CO₂ cylinders. Lightweight, tough, and corrosion-resistant cylinders feature clear-coated brushed aluminum exteriors, thick walls, and installed CGA320 valves.

MODEL	CO ₂ CAPACITY pounds / kg at 68% fill	SERVICE PRESSURE psig / bar	OUTSIDE DIAMETER inches / mm	LENGTH inches / mm	WEIGHT pounds / kg	INLET THREAD
25LBALVLV	2.5 / 1.14	1800 / 124	4.4 / 111	11.0 / 280	3.7 / 166	3/4" -16 UNF -2B
5LBALVLV	5.0 / 2.27	1800 / 124	5.3 / 133	14.2 / 362	7.5 / 3.42	1-1/8" -12 UNF -2B
10LBALVLV	10 / 4.55	1800 / 124	6.9 / 175	16.6 / 422	14.1 / 6.4	1-1/8" -12 UNF -2B
15LBALVLV	15 / 6.82	1800 / 124	6.9 / 175	23.2 / 589	17.0 / 7.71	1-1/8" -12 UNF -2B
20LBALVLV	20 / 9.09	1800 / 124	8.0 / 203	23.3 / 592	24.8 / 11.2	1-1/8" -12 UNF -2B
35LBALVLV	35 / 15.9	1800 / 124	8.0 / 203	38.0 / 966	36.9 / 16.7	1-1/8" -12 UNF -2B
50LBALVLV	50 / 22.7	1800 / 124	8.6 / 218	46.3 / 1177	48.8 / 22.1	1-1/8" -12 UNF -2B



allsafe.net

sales@allsafe.net

866-958-3473

26443 Fallbrook Avenue, Wyoming, MN 55092